



Product Description

Giraffe series is designed for maintenance free, water proof, dust proof, moisture proof and insect proof. The covered glass of display is an optical full-fit process that increases perceived contrast, reduces reflected light, and delivers amazing image quality even in direct sunlight. Operating temperature range is -20°C to 60°C and able to work steadily outdoor all year round. Giraffe series provides 5000nit of brightness output to cope with outdoor ambient lighting conditions. Built-in light sensor automatically adjusts the brightness of the display to optimize power consumption and enhance the viewing experience

Highlights

Patented dynamic system of thermal transfer

Able to maintain proper cooling of internal components under extreme heat conditions.

High brightness output

Providing a light output of 5000nit to cope with high ambient lighting conditions.

Fully hermetic design

The IP65 rating prevents foreign objects such as water, dust, moisture and insects from entering the display.

Impact resistant • Protected by tempered glass lid

Make sure the screen is unaffected by vandalism and debris.

About Shenzhen Spectrum Technology Co., Ltd.

Tel: 0755-28223083 E-mail: sales@spectrum-sz.com Web: www.spectrumdisplay.cn / www.spectrum-sz.com

Spectrum is specializing in customize outdoor/indoor LED and LCD display solutions.

Spectrum has over 10 years of experience in design and manufacture LED/LCD display products.

Spectrum's LED production line are equipped with the latest/most advanced automatic machines and well-equipped devices.

Production line can support monthly production capabilities of 2000 sqm.



@sz-spectrum



Shenzhen_spectrum



shenzhen_spectrum



shenzhen_spectrum



shenzhen_spectrum

SPECTRUM



Giraffe Series

Wall-Mount | Floor Stand | Street Poles | Bus Station

Giraffe series is an outdoor high brightness HD LCD display designed to withstand the rigors of outdoor environments. Crane series designed with IP65 rating and a patented cooling system. Outdoor LCD Cabinet structure can be use for Wall-mount, Floor stand and Street pole.

SPECTRUM

Specifications

Panel Parameters	Parameters	55"
	Display Size	1210 x 680mm
	Aspect Ratio	16:9
	Resolution	1920 x 1080
	Brightness	5,000 cd/m ²
	Protection Rating	IP65



Anti-Reflection



Easy Installation



High Brightness



24/7



Slim depth



IP65



Anti Glare



Cooling System



Narrow Bezel



Catwalk Space free

Specifications

Parameters	32 "	43"	55"	65"	75"	86"
	Resolution	1080x1920	2160x3840 / 1080x1920			
Display Area	393x698mm	530x942mm	680x1210mm	803x1428mm	900x1600mm	1066x1895mm
Aspect Ratio	9:16					
Brightness	≥3000 Nits					
Color Depth	10Bits(1.07 Billion)					
Viewing Angle	(H)178°/(V)178°					
Contrast Ratio	4000:1					
Interface	Input Interface					
	HDMIx1, VGAX1, DP1.2x1, USBx1					
Power Supply	Output Interface					
	RS232x1, Earphonex1					
Environment	Inputs Voltage					
	AC110 ~ 240V (50~60Hz)					
	Rated Power	800	1000			1200
Accessories	Standby Input Power					
	≤5W					
	Operating Temperature					
	-20°C ~ 60°C					
Internal Media Player	Operating Humidity					
	10% ~ 80%					
	Storage Humidity					
5% ~ 90%						
Protection Rating						
IP65						
Included						
AC Power Cable, Remote Control						
Optional						
Touch Screen Upgrade, Network Upgrade, Camera, Speakers, Dynamic Cooling System, Automatic Brightness Sens						
Operating System						
Customisable						